



Gear Oil

Technical Data Sheet (TDS)


HOLSTEIN GL-5

Tajhiz Niroo Zangan is a public stock company and manufacturer of various lubrication products, used in automotive, industrial and marine equipment, including gasoline and diesel engine oils, gear oils, hydraulic fluids, compressor oils, locomotive oils, greases, heavy-duty marine diesel engine oils, trunk piston oils, cylinder oils, antifreeze, ...



SAE 85W-140

API GL-5



Gear Oil

HOLSTEIN* GL-5 is a high-performance gear lubricant, designed to provide excellent lubrication under severe conditions like high-speed/shock load, high-speed/low torque, and/or low-speed, high torque in a wide range of manual automotive transmissions, axles and final drives. HOLSTEIN GL-5 is recommended for on-road passenger cars, light- and heavy-duty trucks, buses and vans, and off-highway equipment in construction, mining and agriculture.

Advantages

- Formulated from high-quality base stocks and balanced extreme pressure (EP) additives
- Superior anti-wear property
- Longer gear and bearings life due to excellent oxidation stability
- Effective rust and corrosion protection
- Good anti-foam property, ensuring film strength for effective lubrication
- Excellent seal compatibility lead to minimize leakage

SAE 85W-140, API GL-5

Specification	Vis @ 100 °C cSt	VI -	Flash Point °C	Pour Point °C (Max)	Density @ 15 °C kg/m ³
Typical	28	99	230	-18	900
ASTM Test Method	D 445	D 2270	D 92	D 97	D 1298

*HOLSTEIN: A powerful, precise and technical horse, monarch of dressage and show jumping